

Knockout Tile

SPECIFICATIONS

Style Number:	KO20122
Plank Size:	12" x 24"
Product Construction:	2.0 mm Flexible LVT
Wear Layer:	12 mil with MaxProtect® Coating
Edge:	SquareEdge™
Gloss Level:	Matte
Installation Method:	Glue Down
Recycled Content:	None
Certifications:	GreenGuard Gold®

Classification	ASTM F1700-20	Class III, Type B
Chemical Resistance	ASTM F 925	Passes
Critical Radiant Flux	ASTM E 648-06	Passes
Dimensional Stability	ASTM F 2199	Passes
Residual Indentation	ASTM F 1914	Passes
Resistance to Heat	ASTM F 1514	Passes
Resistance to Light	ASTM F 1515	Passes
Smoke Density	ASTM E 662	Passes
Thickness, Product	ASTM F 386	Passes
Thickness, Wearlayer	ASTM F410	Passes
Slip Resistance	ANSI A 137	Passes
Flexibility	ASTM F137	Passes
Smoke Density	ASTM E 662	Passes
Slip Resistance	ANSI A 137	Passes
Delta IIC	ASTM E2179-03(2016)	4
Impact Insulation	ASTM E492-09(2016)	43

PACKAGING

Square Feet Per Carton:	54	Pieces Per Carton:	27
Square Feet Per Pallet:	2,808	Cartons Per Pallet:	52
Square Feet Per Container:	56,160	Pallets Per Container:	20
Weight Per Carton:	39.237 lbs	Weight Per Pallet:	2,040.32 lbs

COLOR LINE

20196 Garrett	20198 Fulton
20197 Cambria	20199 Bedford

WARRANTIES

30 Year Limited Residential Wear*	20 Year Limited Light Commercial Wear*
-----------------------------------	--

*Please visit our website for full warranty details.