

Grandview

SPECIFICATIONS

Style Number: GRA50201
Plank Size: 8.748" x 60"
Overall Thickness: 6.0 mm

Product Construction: 5.0 mm SPC + 1.0 mm MaxStepPro™

Wear Layer: 20 mil with MaxProtect®

Edge: NaturalEdge™

Gloss Level: Matte
Installation Method: Floating
Recycled Content: None

Certifications: GreenGuard Gold®

Classification ASTM F3261-20 Class I, Type B, Grade 1, Backing Class B

ASTM F 925 Chemical Resistance Passes Critical Radiant Flux **ASTM E 648-06 Passes Dimensional Stability ASTM F 2199 Passes Residual Indentation ASTM F 1914 Passes Resistance to Heat ASTM F 1514 Passes Resistance to Light ASTM F 1515** Passes **Smoke Density ASTM E 662** Passes

Thickness ASTM F 386 I ASTM F387 Passes I ≥ 6.0mm Pynamic Coefficient of Friction ANSI A137.1 ≥ 40 Wet Result

Wearlayer Thickness ASTM F 410 ≥ 20mil

Static Load Limit ASTM F970 ≥ 500lb/in2 (exceeds ASTM 3261-20)

Squareness ASTM F2421 Passes

Thickness Swell ASTM F3261 ≤1% w/backing (exceeds ASTM 3261-20)

Curling After Exposure to Heat ISO 23999 No Measureable Curl

Dimensional Stability ISO 23999 ≥ .1% (exceeds ASTM 3261-20)

Installed Geometric Characteristics ISO 24337 Passes

PACKAGING

Square Feet Per Carton:21.87Pieces Per Carton:6Square Feet Per Pallet:1312.2Cartons Per Pallet:60Square Feet Per Container:31,070Pallets Per Container:20

Weight Per Carton: 38.57 lbs Weight Per Pallet: 2,314.2 lbs

COLOR LINE

 60101 Jodie
 60103 Layland
 60122 Boone
 60111 Eleverton
 60113 Glen Jean

 60102 Kaymoor
 60121 Alaska
 60123 Claremont
 60112 Fire Creek
 60114 Harvey

WARRANTIES

Lifetime Limited Waterproof* Lifetime Limited Residential Wear* 10 Year Light Commercial Wear*

*Please visit our website for full warranty details.