

RockLock Plus

SPECIFICATIONS

Style Number: RLP42201
Plank Size: 7.09" x 48.03"
Overall Thickness: 5.2 mm

Product Construction: 4.2 mm SPC + 1.0 mm MaxStepPro™

Wear Layer: 20 mil with MaxProtect®

Edge: ColorEdge™ Embossing: GenuWood™

Installation Method: I4F 3L TripleLock® and Click4U®

Recycled Content: None

Certifications: GREENGUARD Gold®

Classification (ASTM 3261-17) Class III, Type B **Chemical Resistance** (ASTM F 925) Passes **Critical Radiant Flux** (ASTM E 648-06) **Passes Dimensional Stability** (ASTM F 2199) Passes **Residual Indentation** (ASTM F 1914) Passes **Resistance to Heat** Passes (ASTM F 1514) **Resistance to Light** (ASTM F 1515) **Passes Smoke Density** Passes (ASTM E 662) **Thickness** (ASTM F 387) **Passes Static Load Limit** (ASTM F 970) **Passes Delta IIC** (ASTM E2197-2003) Λ25 **Impact Insulation** (ASTM E492-09) IIC 60

PACKAGING

Sound Transmission

Square Feet Per Carton: 23.64 **Pieces Per Carton:** 10 Square Feet Per Pallet: 1.418.4 **Cartons Per Pallet:** 60 **Square Feet Per Container:** 25,531.2 **Pallets Per Container:** 17 **Weight Per Carton:** Weight Per Pallet: 42.53 lbs 2,551.8 lbs

(ASTM E90-2009)

∂ COLOR LINE

5037 Cass 5042 Snowshoe 5052 Timberline 5072 Davis 5087 Hinkleville 5038 Durbin 5043 Roanoke 5061 Tunnelton 5081 Bowden 5088 Imperial 5039 Beverly 5044 Shepherdstown 5062 Rowlesburg 5082 Parsons 5089 Kanawha 5086 Goshen 5041 Lewisburg 5051 Wisp 5071 Thomas

WARRANTIES

Lifetime Limited Waterproof* Lifetime Limited Residential* 10 Year Limited Light Commercial*

*Please visit our website for full warranty details.

STC 62