



RockLock Plus II

☞ SPECIFICATIONS

Style Number:	RLP40122
Nominal Plank Size:	7" x 48"
Overall Thickness:	5.0 mm
Product Construction:	4.0 mm SPC + 1.0 mm IXPE Cushion
Wear Layer:	12 mil with Ceramic Bead Enhanced Urethane Coating
Edge:	Four-Sided Color Cut Bevels
Embossing:	Embossed in Register
Installation Method:	I4F 3L TripleLock® and Click4U®
Recycled Content:	None
Certifications:	FloorScore®

Classification	(ASTM 3261-17)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Delta IIC	(ASTM E2197-2003)	Δ25
Impact Insulation	(ASTM E492-09)	IIC 60
Sound Transmission	(ASTM E90-2009)	STC 62

☞ PACKAGING

Square Feet Per Carton:	23.64	Pieces Per Carton:	10
Square Feet Per Pallet:	1,418.4	Cartons Per Pallet:	60
Square Feet Per Container:	25,531.2	Pallets Per Container:	18
Weight Per Carton:	38.93 lbs	Weight Per Pallet:	2,385.8 lbs

☞ COLOR LINE

5041 Lewisburg	5044 Shepherdstown	5061 Tunnelton	5072 Davis
5042 Snowshoe	5051 Wisp	5062 Rowlesburg	5081 Bowden
5043 Roanoke	5052 Timberline	5071 Thomas	5082 Parsons

☞ WARRANTIES

Lifetime Limited Waterproof*	Lifetime Limited Residential*	10 Year Limited Commercial*
------------------------------	-------------------------------	-----------------------------

*Please visit our website for full warranty details.