



RigidLock Plus

☞ SPECIFICATIONS

Style Number:	RP415203
Plank Size:	7.01" x 47.91"
Overall Thickness:	6.5 mm
Product Construction:	4.0 mm Core + 1.5 mm Vinyl Top + 1.0 mm IXPE Cushion
Wear Layer:	20 mil with Ceramic Bead Enhanced Urethane Coating
Edge:	Four-Sided Color Cut Bevels*
Embossing:	Embossed in Register*
Installation Method:	Uniclic® Angle-Tap
Recycled Content:	None
Certifications:	FloorScore®

Classification	(ASTM F1700-04)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Delta IIC	(ASTM E2197-2003)	TBD
Impact Insulation	(ASTM E492-09)	IIC 66
Sound Transmission	(ASTM E90-2009)	TBD

☞ PACKAGING

Square Feet Per Carton:	23.32	Pieces Per Carton:	10
Square Feet Per Pallet:	1,632.40	Cartons Per Pallet:	70
Square Feet Per Container:	32,648	Pallets Per Container:	20
Weight Per Carton:	36.50 lbs	Weight Per Pallet:	2,555 lbs

☞ COLOR LINE

6501 Fairfax	6504 Austin*	6511 Chesapeake	6514 Ticonderoga
6502 Lexington	6506 Lafayette	6512 Princeton	6515 Yorktown
6503 Concord	6508 Hamilton	6513 Saratoga	

☞ WARRANTIES

Lifetime Limited Waterproof**	Lifetime Limited Residential*	10 Year Limited Commercial*
-------------------------------	-------------------------------	-----------------------------

* Austin features the following changes: Edge: Four-Sided Micro-Bevel and Embossing: Hand-Scraped Texture **Please visit our website for full warranty details.