



RigidLock Plus Tile

☞ SPECIFICATIONS

Style Number:	RP415202
Plank Size:	11.65" x 23.46"
Overall Thickness:	6.5 mm
Product Construction:	4.0 mm Core + 1.5 mm Vinyl Top + 1.0 mm IXPE Cushion
Wear Layer:	20 mil with Ceramic Bead Enhanced Urethane Coating
Edge:	Four-Sided Color Cut Bevels
Embossing:	Slate Texture
Installation Method:	Uniclic® Angle-Tap
Recycled Content:	None
Certifications:	FloorScore®

Classification	(ASTM F1700-04)	Class III, Type B
Chemical Resistance	(ASTM F 925)	Passes
Critical Radiant Flux	(ASTM E 648-06)	Passes
Dimensional Stability	(ASTM F 2199)	Passes
Residual Indentation	(ASTM F 1914)	Passes
Resistance to Heat	(ASTM F 1514)	Passes
Resistance to Light	(ASTM F 1515)	Passes
Smoke Density	(ASTM E 662)	Passes
Thickness	(ASTM F 387)	Passes
Static Load Limit	(ASTM F 970)	Passes
Delta IIC	(ASTM E2197-2003)	Δ25
Impact Insulation	(ASTM E492-09)	IIC 60
Sound Transmission	(ASTM E90-2009)	STC 62

☞ PACKAGING

Square Feet Per Carton:	22.79	Pieces Per Carton:	12
Square Feet Per Pallet:	1,093.92	Cartons Per Pallet:	48
Square Feet Per Container:	31,723.68	Pallets Per Container:	29
Weight Per Carton:	31.50 lbs	Weight Per Pallet:	1,512.00

☞ COLOR LINE

6525 Upshur	6528 Frostburg
6526 Webster	
6527 Frederick	

☞ WARRANTIES

Lifetime Limited Waterproof**	Lifetime Limited Residential*	10 Year Limited Commercial*
-------------------------------	-------------------------------	-----------------------------

**Please visit our website for full warranty details.